




## Radar Water Level System



[www.pizzi-instruments.it](http://www.pizzi-instruments.it)

Instruments and Systems for Geotechnical and Structural Monitoring

## Radar Water Level System



### Description

The Radar Water Level System is a sensor suitable for measurements in large tanks and small channels and for the measurement of small and large flows. Available with different scales, it allows precise and reliable measurement and no contact with the liquid being monitored.

Particularly suitable for level measurements in static situations, it can also be equally effective for measuring liquids in dynamic regimes.

Measurement is independent of the type of liquid measured and its density.

### Applications

This instrument is particularly suitable for monitoring levels in tunnels of concrete, RCC and in earth dams and for the monitoring of leakage and drainage. Also used for measurement of levels in basins.

Especially recommended for:

- Lakes
- Wells
- Tanks
- Harbors
- Docks
- Channels
- Streams
- Rivers
- Others

## Features and benefits

The Radar Water Level System allows the measurement of levels also in dynamic conditions.

The instrument is characterized by:

- Non-contact measurement
- Easy installation
- No wear and tear
- Requires no maintenance
- Pressure independent
- Temperature independent
- High measuring accuracy including high range
- Available with analog and digital outputs
- Can be integrated with GPRS transmitter

## Measuring principle

Extremely short microwave pulses are radiated by the antenna system to the product to be measured. They are then reflected by the product's surface and received back by the antenna system.

The round-trip time of the signals is proportional to the level.

A special processing procedure ensures reliable and precise measurement.

## Technical specifications

Measuring Ranges	Encapsulated antenna system up to 10 meters; Plastic horn antenna up to 20 meters; Parabolic antenna up to 70 meters
Connection	Thread G1½, 1½ NPT Mounting bracket Flange DN 80, 2 "
Measuring Deviation	± 2 mm
Temperature	-40 ... +80 °C
Pressure	-1 ... +2 bar (-100 ... +200 kPa)
Storage temperature and transport	-40+80 °C
Operating voltage	9,6 Vdc....36 Vdc
Output	4-20mA modbus


## Accessories and related products

Device of application and support	For application on vertical or horizontal walls
Group of over-voltage protection	Electrical protection

## The Company

For over 40 years we have been producing precision and large facility monitoring instruments sold throughout the world.

Accuracy in design, efficiency in construction, reliability in management; these are the prerogatives that every major work must have and that Structural Monitoring Systems must guarantee.



### Technical assistance

If you have any requests or questions about our instruments or if you have special needs that require different solutions from the standard, please contact us. Our team will provide all the necessary information and will be very happy to work with you to study, develop and customize instruments and solutions suitable for your specific needs.

All data present in the sheets could change without notice.

Please check the release carefully and for more details contact Pizzi Instruments.

**Pizzi Instruments S.r.l.**  
Via del Fornaccio, 46  
50012 - Vallina - FI - Italia

Phone/Fax : +39 055 6810722  
[info@pizzi-instruments.it](mailto:info@pizzi-instruments.it)  
[www.pizzi-instruments.it](http://www.pizzi-instruments.it)

